

Technical Self-Declaration

This sheet must be fully completed and handed to the Technical Inspection Personnel at the time announced at the event.



Front Tires 1. BarCode No. 2. BarCode Rear Tires 1. BarCode No. 2. BarCode Driver Protection Helmet: Full Coverage (Full Face) with vision compliance with current ASN Karting Regulations – Book Rib Protector: Unaltered designed for motorsport under Protection: Balaclava/head-sock required if hair extends beneath helmet leven Competition Numbers and Number Panels: Number Panels: (4): 1-Front center, 2-Sides vertical, 1-Rear. Yellow background Numbers: Black – Min. 6" (15 cm) high, 1" (2.5 cm) wide stroke. Cadet Min. 5" (13 cm) high Chassis Frame Condition and Chassis Welds: No visible cracking Axles and Bearings: No excessive place Wheels & Tires: No visible damang Steering Components: No excessive place Mounting and Supports: No visible cracking Bodywork Mounting and Supports: Securely fastened as per Regulation Ballast Weights: Properly secured Brakes: Proper function. Adequate brake pad thickness. No visible cracking Chain/Oil Guard: Must be in place and as per Regulation Throttle: Throttle not sticking. Return spring operator Fluids Fuel System: Tank, mounts, lines and caled Chain Chains: Hoses/connectors: brake, water, oil. Breathers and catch cans - clamps a				Fill in fo	orm completely	. Print in BLO	CK lett	ers.			
Serial No: (2 cycle - per class regulations)	Driver Name:			Class:						Kart No:	
Seal No.	Chasis Make/Model:		1.			ı	Serial No:				
Engine Make/Model: (All Briggs & Stratton classes one engine only) Information below to be completed if required in Supplimentary Front Tires 1. BarCode No. 2. BarCode Rear Tires 1. BarCode No. 2. BarCode Rear Tires 1. BarCode No. 2. BarCode Rear Tires 1. BarCode No. 2. BarCode Poliver Protection Helmet: Full Coverage (Full Face) with vis In compliance with current ASN Karting Regulations – Book Rib Protector: Unaltered designed for motorsport und Drivers Suit and Apparel: Karting design. Abrasion resistant shoes and glow Long Hair Protection: Balaclava/head-sock required if hair extends beneath helmet leven to the competition Numbers and Number Panels: Number Panels: (4): 1-Front center, 2-Sides vertical, 1-Rear. Yellow background Numbers: Black – Min. 6" (15 cm) high, 1" (2.5 cm) wide stroke. Cadet Min. 5" (13 cm) higher Chassis Frame Condition and Chassis Welds: No visible cracking Axles and Bearings: No excessive plus Wheels & Tires: No visible cracking Axles and Bearings: No excessive plus Seat Mounting and Supports: No excessive plus Bodywork Mounting and Supports: Securely fastened as per Regulation Ballast Weights: Property secure Brakes: Proper function. Adequate brake pad thickness. No visible cracking Chain/Oil Guard: Must be in place and as per Regulation Throttle: Throttle: Throttle: Throttle: Throttle: Trank, mounts, lines and components: Hoses/connectors: brake, water, oil. Breathers and catch cans - clamps a mounting components entered and used in the competition at all times meets the technical requirements.	Engine Make/Model:			Serial No:							
Engine Make/Model: (All Briggs & Stratton classes one engine only) Information below to be completed if required in Supplimentary Front Tires 1. BarCode No. 2. BarCode Rear Tires 1. BarCode No. 2. BarCode Rib Protector: Unaltered designed for motorsport under the current ASN Karting Regulations — Book Rib Protector: Unaltered designed for motorsport under the competition Number Sunt Apparel: Karting design. Abrasion resistant shoes and glow Long Hair Protection: Balaclava/head-sock required if hair extends beneath helmet lev Competition Numbers and Number Panels Number Panels: (4): 1-Front center, 2-Sides vertical, 1-Rear. Yellow background Numbers: Black — Min. 6" (15 cm) high, 1" (2.5 cm) wide stroke. Cadet Min. 5" (13 cm) high Chassis Frame Condition and Chassis Welds: No visible cracking Axles and Bearings: No excessive pl Wheels & Tires: No visible damated Steering Components: No visible cracking Bodywork Mounting and Supports: Securely fastened as per Regulation Ballast Weights: Properly secured Brakes: Proper function. Adequate brake pad thickness. No visible cracking Chain/Oil Guard: Must be in place and as per Regulation Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and carried the competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requite entire race event.	(2 cycle - per class regulations)		1.				Sor	al No			
Seal No.											
Information below to be completed if required in Supplimentary Front Tires 1. BarCode No. 2. BarCode Rear Tires 1. BarCode No. 2. BarCode Driver Protection Helmet: Full Coverage (Full Face) with vis In compliance with current ASN Karting Regulations – Book Rib Protector: Unaltered designed for motorsport u Drivers Suit and Apparel: Karting design. Abrasion resistant shoes and glow Long Hair Protection: Balaclava/head-sock required if hair extends beneath helmet leven to the competition Numbers and Number Panels Number Panels: (4): 1-Front center, 2-Sides vertical, 1-Rear, Yellow backgroun Numbers: Black – Min. 6" (15 cm) high, 1" (2.5 cm) wide stroke. Cadet Min. 5" (13 cm) high Chassis Frame Condition and Chassis Welds: No visible cracking Axles and Bearings: No excessive plents of the components: No excessive plents of the components of	(All Briggs & Stratton		2.				Seri	al No.			
Front Tires 1. BarCode No. Rear Tires 1. BarCode No. 2. BarCode Driver Protection Helmet: Full Coverage (Full Face) with vis In compliance with current ASN Karting Regulations – Book Rib Protector: Unattered designed for motorsport u Drivers Suit and Apparel: Karting design. Abrasion resistant shoes and glov Long Hair Protection: Balaclava/head-sock required if hair extends beneath helmet lev Competition Numbers and Number Panels Number Panels: (4): 1-Front center, 2-Sides vertical, 1-Rear. Yellow backgrous Numbers: Black – Min. 6" (15 cm) high, 1" (2.5 cm) wide stroke. Cadet Min. 5" (13 cm) hig Chassis Frame Condition and Chassis Welds: No visible crackis Axles and Bearings: No excessive pl Wheels & Tires: No visible dama Steering Components: No excessive pl Seat Mounting and Supports: Securely fastened as per Regulatio Ballast Weights: Properly secure Brakes: Proper function. Adequate brake pad thickness. No visible crackis Chain/Oil Guard: Must be in place and as per Regulatio Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and care fluids and components entered and used in the competition at all times meets the technical requition and components entered and used in the competition at all times meets the technical requition and components entered and used in the competition at all times meets the technical requition and components entered and used in the competition at all times meets the technical requition and components entered and used in the competition at all times meets the technical requition and components entered and used in the competition at all times meets the technical requition and components entered and used in the competition at all times meets the technical requition and components entered and used in the competition at all times meets the technical requition and componen				Seal No.							
Driver Protection Helmet: Full Coverage (Full Face) with vis In compliance with current ASN Karting Regulations — Book Rib Protector: Unaltered designed for motorsport unaltered and used in the competition at all times it is the competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requition entered and used in the competition at all times meets the technical requition and components entered and used in the competition at all times meets the technical requition and components entered and used in the competition at all times meets the technical requition and components entered and used in the competition at all times meets the technical requition and components entered and used in the competition at all times meets the technical requition and components entered and used in the competition at all times meets the technical requition and components entered and used in the competition at all times meets the technical requition and components entered and used in the competition at all t	Information below to be completed if required in Supplimentary Regulations.										
Driver Protection Helmet: Full Coverage (Full Face) with vis In compliance with current ASN Karting Regulations – Book Rib Protector: Unaltered designed for motorsport un Drivers Suit and Apparel: Karting design. Abrasion resistant shoes and glow Long Hair Protection: Balaclava/head-sock required if hair extends beneath helmet leving Competition Numbers and Number Panels Number Panels: (4): 1-Front center, 2-Sides vertical, 1-Rear. Yellow backgroung Numbers: Black – Min. 6" (15 cm) high, 1" (2.5 cm) wide stroke. Cadet Min. 5" (13 cm) high Chassis Frame Condition and Chassis Welds: No visible cracking Axles and Bearings: No excessive plus Wheels & Tires: No visible damages Steering Components: No excessive plus Seat Mounting and Supports: No visible cracking Bodywork Mounting and Supports: Securely fastened as per Regulation Ballast Weights: Properly secured Brakes: Proper function. Adequate brake pad thickness. No visible cracking Chain/Oil Guard: Must be in place and as per Regulation Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and cancer Fluid Lines: Hoses/connectors: brake, water, oil. Breathers and catch cans - clamps a mounting the entire race event.	Front Tires	1.	В	arCode No.			2.	2. BarCode No.			
Helmet: Full Coverage (Full Face) with vis In compliance with current ASN Karting Regulations – Book Rib Protector: Unaltered designed for motorsport u Drivers Suit and Apparel: Karting design. Abrasion resistant shoes and glov Long Hair Protection: Balaclava/head-sock required if hair extends beneath helmet lev Competition Numbers and Number Panels Number Panels: (4): 1-Front center, 2-Sides vertical, 1-Rear. Yellow backgroun Numbers: Black – Min. 6" (15 cm) high, 1" (2.5 cm) wide stroke. Cadet Min. 5" (13 cm) hig Chassis Frame Condition and Chassis Welds: No visible crackin Axles and Bearings: No excessive pl Wheels & Tires: No visible damay Steering Components: No excessive pl Seat Mounting and Supports: No visible crackin Bodywork Mounting and Supports: Securely fastened as per Regulatio Ballast Weights: Properly secure Brakes: Proper function. Adequate brake pad thickness. No visible crackin Chain/Oil Guard: Must be in place and as per Regulatio Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and ca Fluid Lines: Hoses/connectors: brake, water, oil. Breathers and catch cans - clamps a mountii Competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requite entire race event.	Rear Tires	1.	В	arCode No.			2.	BarCode	No.		
Helmet: Full Coverage (Full Face) with vis In compliance with current ASN Karting Regulations – Book Rib Protector: Unaltered designed for motorsport u Drivers Suit and Apparel: Karting design. Abrasion resistant shoes and glov Long Hair Protection: Balaclava/head-sock required if hair extends beneath helmet lev Competition Numbers and Number Panels Number Panels: (4): 1-Front center, 2-Sides vertical, 1-Rear. Yellow backgroun Numbers: Black – Min. 6" (15 cm) high, 1" (2.5 cm) wide stroke. Cadet Min. 5" (13 cm) hig Chassis Frame Condition and Chassis Welds: No visible crackin Axles and Bearings: No excessive pl Wheels & Tires: No visible damay Steering Components: No excessive pl Seat Mounting and Supports: No visible crackin Bodywork Mounting and Supports: Securely fastened as per Regulatio Ballast Weights: Properly secure Brakes: Proper function. Adequate brake pad thickness. No visible crackin Chain/Oil Guard: Must be in place and as per Regulatio Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and ca Fluid Lines: Hoses/connectors: brake, water, oil. Breathers and catch cans - clamps a mountii Competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requite entire race event.											
In compliance with current ASN Karting Regulations – Book Rib Protector: Unaltered designed for motorsport u Drivers Suit and Apparel: Karting design. Abrasion resistant shoes and glow Long Hair Protection: Balaclava/head-sock required if hair extends beneath helmet lev Competition Numbers and Number Panels Number Panels: (4): 1-Front center, 2-Sides vertical, 1-Rear. Yellow backgroun Numbers: Black – Min. 6" (15 cm) high, 1" (2.5 cm) wide stroke. Cadet Min. 5" (13 cm) high Chassis Frame Condition and Chassis Welds: No visible crackin Axles and Bearings: No excessive pl Wheels & Tires: No visible damage Steering Components: No excessive pl Seat Mounting and Supports: No visible crackin Bodywork Mounting and Supports: Securely fastened as per Regulatio Ballast Weights: Properly secure Brakes: Proper function. Adequate brake pad thickness. No visible crackin Chain/Oil Guard: Must be in place and as per Regulatio Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and cancellation Fluid Lines: Hoses/connectors: brake, water, oil. Breathers and catch cans - clamps a mountin Competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requition entire race event.				Driver P	rotection					Competitor	
In compliance with current ASN Karting Regulations – Book Rib Protector: Unaltered designed for motorsport u Drivers Suit and Apparel: Karting design. Abrasion resistant shoes and glow Long Hair Protection: Balaclava/head-sock required if hair extends beneath helmet lev Competition Numbers and Number Panels Number Panels: (4): 1-Front center, 2-Sides vertical, 1-Rear. Yellow backgroun Numbers: Black – Min. 6" (15 cm) high, 1" (2.5 cm) wide stroke. Cadet Min. 5" (13 cm) high Chassis Frame Condition and Chassis Welds: No visible crackin Axles and Bearings: No excessive pl Wheels & Tires: No visible damage Steering Components: No excessive pl Seat Mounting and Supports: No visible crackin Bodywork Mounting and Supports: Securely fastened as per Regulatio Ballast Weights: Properly secure Brakes: Proper function. Adequate brake pad thickness. No visible crackin Chain/Oil Guard: Must be in place and as per Regulatio Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and cancellation Fluid Lines: Hoses/connectors: brake, water, oil. Breathers and catch cans - clamps a mountin Competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requition entered and used in the competition at all times meets the technical requition entered and used in the competition at all times meets the technical requition entered and used in the competition at all times meets the technical requition entered and used in the competition at all times meets the technical requition entered and used in the competition at all times meets the technical requition entered and used in the competition at all times meets the technical requition entered and used in the competition at all times and cancellation.	Helmet: Full Coverage (Full Face) with visor.								Checked & OK √		
Drivers Suit and Apparel: Karting design. Abrasion resistant shoes and glow Long Hair Protection: Balaclava/head-sock required if hair extends beneath helmet lev Competition Numbers and Number Panels Number Panels: (4): 1-Front center, 2-Sides vertical, 1-Rear. Yellow backgroun Numbers: Black – Min. 6" (15 cm) high, 1" (2.5 cm) wide stroke. Cadet Min. 5" (13 cm) high Chassis Frame Condition and Chassis Welds: No visible crackin Axles and Bearings: No excessive pl. Wheels & Tires: No visible damage Steering Components: No excessive pl. Seat Mounting and Supports: No visible crackin Bodywork Mounting and Supports: Securely fastened as per Regulatio Ballast Weights: Properly secure Brakes: Proper function. Adequate brake pad thickness. No visible crackin Chain/Oil Guard: Must be in place and as per Regulatio Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and cater Chain System: Tank, mounts, lines and cater Competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requitine entire race event.					e with current A	SN Karting Re	gulatio	ns – Book 1			
Long Hair Protection: Balaclava/head-sock required if hair extends beneath helmet leve Competition Numbers and Number Panels Number Panels: (4): 1-Front center, 2-Sides vertical, 1-Rear. Yellow background Numbers: Black – Min. 6" (15 cm) high, 1" (2.5 cm) wide stroke. Cadet Min. 5" (13 cm) high Chassis Frame Condition and Chassis Welds: No visible cracking Axles and Bearings: No excessive planels & Tires: No visible damage Steering Components: No excessive planels & Tires: No visible cracking Bodywork Mounting and Supports: Securely fastened as per Regulation Ballast Weights: Properly secure Brakes: Proper function. Adequate brake pad thickness. No visible cracking Chain/Oil Guard: Must be in place and as per Regulation Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and carried times: Hoses/connectors: brake, water, oil. Breathers and catch cans - clamps a mountiing Competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requitate entire race event.											
Competition Numbers and Number Panels Number Panels: (4): 1-Front center, 2-Sides vertical, 1-Rear. Yellow background Numbers: Black – Min. 6" (15 cm) high, 1" (2.5 cm) wide stroke. Cadet Min. 5" (13 cm) high Chassis Frame Condition and Chassis Welds: No visible cracking Axles and Bearings: No excessive plus Wheels & Tires: No visible damaged Steering Components: No excessive plus Seat Mounting and Supports: No visible cracking Bodywork Mounting and Supports: Securely fastened as per Regulation Ballast Weights: Properly secured Brakes: Proper function. Adequate brake pad thickness. No visible cracking Chain/Oil Guard: Must be in place and as per Regulation Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and cate System: Tank, mounts, lines and cate Competitor's Pluid Lines: Hoses/connectors: brake, water, oil. Breathers and catch cans - clamps a mountiin Competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requitate entire race event.											
Number Panels: (4): 1-Front center, 2-Sides vertical, 1-Rear. Yellow background Numbers: Black – Min. 6" (15 cm) high, 1" (2.5 cm) wide stroke. Cadet Min. 5" (13 cm) high Chassis Frame Condition and Chassis Welds: No visible cracking Axles and Bearings: No excessive plus Wheels & Tires: No visible damage Steering Components: No excessive plus Seat Mounting and Supports: No visible cracking Bodywork Mounting and Supports: Securely fastened as per Regulation Ballast Weights: Properly secured Brakes: Proper function. Adequate brake pad thickness. No visible cracking Chain/Oil Guard: Must be in place and as per Regulation Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and cate System: Tank, mounts, lines and cate Competitor's Pluids Fuel System: Tank, mounts, lines and cate Competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requitate entire race event.					-		rioutii				
Chassis Frame Condition and Chassis Welds: No visible crackin Axles and Bearings: No excessive ple Wheels & Tires: No visible damage Steering Components: No excessive ple Seat Mounting and Supports: No visible crackin Bodywork Mounting and Supports: Securely fastened as per Regulatio Ballast Weights: Properly secure Brakes: Proper function. Adequate brake pad thickness. No visible crackin Chain/Oil Guard: Must be in place and as per Regulatio Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and cate Fluid Lines: Hoses/connectors: brake, water, oil. Breathers and catch cans - clamps a mountin Competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requitite entire race event.							Yellow	background			
Frame Condition and Chassis Welds: No visible cracking Axles and Bearings: No excessive please and Steering Components: No excessive please and Supports: No visible damage and Supports: No visible cracking Bodywork Mounting and Supports: Securely fastened as per Regulation Ballast Weights: Properly secured Brakes: Proper function. Adequate brake pad thickness. No visible cracking Chain/Oil Guard: Must be in place and as per Regulation Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and cate for the System: Tank, mounts, lines and cate for the System: Tank, mounts, lines and cate for the System: Tank, mounts and cate for	Numbers: Black – Min. 6" (15 cm) high, 1" (2.5 cm) wide stroke. Cadet Min. 5" (13 cm) high.										
Axles and Bearings: No excessive planels & Tires: No visible damage Steering Components: No excessive planels & Tires: No visible damage Steering Components: No excessive planels & Mounting and Supports: No visible cracking Bodywork Mounting and Supports: Securely fastened as per Regulation Ballast Weights: Properly secured Brakes: Proper function. Adequate brake pad thickness. No visible cracking Chain/Oil Guard: Must be in place and as per Regulation Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and carried the Competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requitate entire race event.											
Wheels & Tires: No visible damage Steering Components: No excessive place of Mounting and Supports: No visible cracking Bodywork Mounting and Supports: Securely fastened as per Regulation Ballast Weights: Properly secured Brakes: Proper function. Adequate brake pad thickness. No visible cracking Chain/Oil Guard: Must be in place and as per Regulation Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and carried the System: Tank, mounts, lines and carried	Frame Condition and Chassis Welds: No visible cracking.										
Steering Components: No excessive place Seat Mounting and Supports: No visible cracking Bodywork Mounting and Supports: Securely fastened as per Regulation Ballast Weights: Properly secured Brakes: Proper function. Adequate brake pad thickness. No visible cracking Chain/Oil Guard: Must be in place and as per Regulation Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and cate Fluid Lines: Hoses/connectors: brake, water, oil. Breathers and catch cans - clamps a mounting Competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requition entire race event.	Axles and Bearings: No excessive play.										
Seat Mounting and Supports: No visible cracking Bodywork Mounting and Supports: Securely fastened as per Regulation Ballast Weights: Properly secured Brakes: Proper function. Adequate brake pad thickness. No visible cracking Chain/Oil Guard: Must be in place and as per Regulation Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and cate the canses of the competitor's brake, water, oil. Breathers and catch canses of mounting the competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requition the entire race event.	Wheels & Tires: No visible damage.										
Bodywork Mounting and Supports: Securely fastened as per Regulation Ballast Weights: Properly secure Brakes: Proper function. Adequate brake pad thickness. No visible cracking Chain/Oil Guard: Must be in place and as per Regulation Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and carried the secure of the s											
Ballast Weights: Properly secure Brakes: Proper function. Adequate brake pad thickness. No visible crackin Chain/Oil Guard: Must be in place and as per Regulation Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and ca Fluid Lines: Hoses/connectors: brake, water, oil. Breathers and catch cans - clamps a mountiin Competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requitite entire race event.											
Brakes: Proper function. Adequate brake pad thickness. No visible cracking. Chain/Oil Guard: Must be in place and as per Regulation. Throttle: Throttle not sticking. Return spring operation. Fluids Fuel System: Tank, mounts, lines and carried the still be stil											
Throttle: Throttle not sticking. Return spring operation Fluids Fuel System: Tank, mounts, lines and ca Fluid Lines: Hoses/connectors: brake, water, oil. Breathers and catch cans - clamps a mountii Competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requitive entire race event.	Bra										
Fluids Fuel System: Tank, mounts, lines and catch cans - clamps a mounting Competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requition at entered event.	Chain/Oil Guard: Must be in place and as per Regulations.										
Fluid Lines: Hoses/connectors: brake, water, oil. Breathers and catch cans - clamps a mountii Competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requitible entire race event.				Throttl	e: Throttle not	sticking. Return	spring	operational			
Fluid Lines: Hoses/connectors: brake, water, oil. Breathers and catch cans - clamps a mountii Competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requitible entire race event.				Flu	ids					_	
Competitor's Declaration: The undersigned acknowledges that at all times it is the competitor's karts and components entered and used in the competition at all times meets the technical requithe entire race event.											
karts and components entered and used in the competition at all times meets the technical requithe entire race event.	Fluid Lines: Hoses/connectors: brake, water, oil. Breathers and catch cans - clamps and mounting.										
Print Name Clearly:	carts and components ent he entire race event. Driver/Mecha	tered nic	l and Sigr	used in the co							